

# EU type examination certificate

## EU-Baumusterprüfbescheinigung

**CE-0085CN0133**

Product Identification No.  
Produkt-Identnummer

<b>Field of Application</b> <i>Anwendungsbereich</i>	EU Gas Appliances Regulation (EU/2016/426) <i>EU-Gasgeräteverordnung (EU/2016/426)</i>
<b>Owner of Certificate</b> <i>Zertifikatinhaber</i>	BFI-Automation Mindermann GmbH Rügenstraße 7, D-42579 Heiligenhaus
<b>Distributor</b> <i>Vertreiber</i>	BFI-Automation Mindermann GmbH Rügenstraße 7, D-42579 Heiligenhaus
<b>Product Category</b> <i>Produktart</i>	Accessories for gas appliances/pressure equipment: Flame supervisor device (4131)
<b>Product description</b> <i>Produktbezeichnung</i>	UV- compact flame supervisor device for gas-burners with intermittent operation
<b>Model</b> <i>Modell</i>	IFC...; IFR...
<b>Countries of Destination</b> <i>Bestimmungsländer</i>	AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MT, NL, NO, PL, PT, RO, SE, SI, SK
<b>Test reports</b> <i>Prüfberichte</i>	Type testing: GA 43 2017 B15 from 11.01.2018 (TRG) Supplement test: GA 43 2017 E14 from 11.01.2018 (TRG)
<b>Test basis</b> <i>Prüfgrundlagen</i>	EU/2016/426 A III B (09.03.2016) DIN EN 298 (01.11.2012)

**Date of Expiry / File No.** 19.02.2028 / 24-0104-GER  
**Ablaufdatum / AZ**

70226-04-A-DE

22.03.2024 Bd A-1/2

Date, Issued by, Sheet, Head of Certification Body  
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH - notified by the government of the Federal Republic of Germany and officially registered by the European Commission for conformity assessment of gas appliances

DVGW CERT GmbH – von der Deutschen Bundesregierung benannte und von der Europäischen Kommission offiziell registrierte Stelle für die Konformitätsbewertung von Gasgeräten

DVGW CERT GmbH  
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3  
53123 Bonn

Tel. +49 228 91 88 - 888

Fax +49 228 91 88 - 993

www.dvgw-cert.com

info@dvgw-cert.com

**Elektrical Data** 230 V AC, 50/60 Hz, IP65  
**Elektrische Daten** 120 V AC, 50/60 Hz, IP65

<b>Type</b> <i>Typ</i>	<b>Technical Data</b> <i>Technische Daten</i>	<b>Remarks</b> <i>Bemerkungen</i>
IFC 10; IFC 11; IFC 50; IFR 10; IFR 11; IFR 50	Ambient temperature range: -20...+60 °C	

<b>Type Variation</b> <i>Ausführungsvariante</i>	<b>Explanations</b> <i>Erläuterungen</i>
...10	UV- compact flame supervisor device for gas-burners with intermittent operation
...11	as ...10 but additional with flame check after shutdown
...50	with relay output
...C...	axial direction of sight of the UV tube
...R...	radial direction of sight of the UV tube

